

DIAMOND BRITE®

EXPOSED AGGREGATE POOL FINISH

DESCRIPTION:

Diamond Brite Finishes are blends of selected quartz aggregates and fortified white portland cement ideal for new or re-finished swimming pools. Available in a variety of colors and textures, Diamond Brite finishes are factory blended to provide the pool owner with an extremely durable and attractive alternative to traditional pool coatings.

ADVANTAGES:

- Superior Bonding
- High strength and rapid curing
- Extremely etch resistant
- Ease of application
- Aggregate exposure easily controlled
- Pumpable

SURFACE PREPARATION:

New Pools: Pool surface must be free of dirt, oil grease or other foreign materials.

Re-finished pools should be undercut 2" below the tile line and a minimum of ½" around main drains. Light fixtures, and return lines. SGM Bond Kote is an excellent surface preparation for re-finishing. Lightly moisten walls and floors prior to application of Diamond Brite.

MIXING:

Thoroughly mix Diamond Brite to a homogeneous lump-free consistency using 1-1/2-2gallons of portable water per 80 lb. bag.

APPLICATION:

Diamond Brite should be applied to a uniform thickness of 3/8" to ½" over the entire surface. The walls may be scratch coated followed by a finish coat or single coated. Material applied to the floor after the walls have been applied, may be accelerated with Accelerator 100 to assure uniform setting time throughout the pool surface.

AGGREGATE EXPOSURE:

Diamond Brite aggregates may be exposed by a variety of techniques. Light water washing followed by a cleaning solution is generally used. Contact your SGM representative for more information on these methods.

COVERAGE:

Each 80 lb. bag will cover approximately 22 sq. ft. , to a thickness of 3/8". Surface roughness affects coverage rates.

PACKAGING:

4 ply heavy duty poly-lined bag, net wt. 80 lb.

CAUTION:

WARNING - EYE IRRITANT CONTAINS PORTLAND CEMENT

Product is alkaline on contact with water. Avoid splashing into eyes or contact with skin. During mixing or application avoid contact with eyes. In case of such contact, flood eyes repeatedly with water and call physician. Wash thoroughly after handling and before smoking or eating. Do not take internally. Contains free Silica. Avoid breathing dust. Prolonged exposure to dust may cause delayed lung disease (Silicosis). Wear NIOSH approved mask for Silica dust. KEEP OUT OF REACH OF CHILDREN.

SHELF LIFE:

One year in unopened properly stored container.

LIMITED WARRANTY:

S.G.M., Inc., will replace any material proved defective with the maximum shelf life on unused material of up to one (1) year. If our products are not found to conform to our high standard, notify S.G.M., Inc., immediately in writing. There is no other obligation expressed or implied and we assume no liabilities for damages of any kind. Suitability of the product for an intended use shall be solely up to the user.

SGM

Pompano Beach, FL – Dallas, TX – Corona, CA – Plant City, FL

Phone: 800.641.9247

1502 SW 2nd Place, Pompano Beach, FL 33069

FAX: 954.943-2402

www.sgm.cc